Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: BPE480VB

External Battery Pack for Select 3-Phase UPS Systems

Highlights

- BPE480VB is an "empty" version of the Tripp Lite BP480V26B external battery pack
- Requires 40 user-supplied 12V 26AH batteries (BB Battery BP26-12 B1 or equal)
- Extends runtime of compatible Tripp Lite UPS Systems using +/- 240VDC configuration
- External battery case matches the appearance of compatible Tripp Lite UPS systems; includes all required wiring and accessories for installation of internal batteries
- Empty configuration greatly reduces worldwide shipping costs
- Hardwire internal batteries and connection to UPS

Description

BPE480VB is an "empty" version of the Tripp Lite BP480V26B external battery pack that requires 40 user-supplied 12V 26AH batteries. Compatible with BB Battery model BP26-12 batteries with B1 type terminals (or equal). External battery case matches the appearance of compatible Tripp Lite UPS systems and includes all required wiring and installation accessories, except batteries. Offers extended battery runtime for critical connected loads. Includes internal disconnect for battery isolation. Multiple BP480V26B / BPE480VB cabinets can be daisy-chained to the UPS for even longer extended run operation.

Compatible UPS Systems: SU40K, SU60K, SU80K, SU20KX, SU40KX, SU60KX, SU80KX, SU60KTV and SU80KTV only.

Applications

- Ideal way to lengthen the battery runtime provided by compatible Tripp Lite UPS systems.

Package Includes

- BPE480VB External Battery Pack
- Warranty information
- Owner's Manual

Specifications

BATTERY	
Expandable battery runtime	Multiple battery packs can be daisy-chained to the UPS for extended runtime
DC system voltage (VDC)	240

Battery Access	Empty-case configuration without pre-installed internal batteries requires a quantity of 40 user-supplied 12 volt, 26 amp-hour batteries with B1 terminals. Model number BP26-12 batteries with B1 bolt and nut compatible terminals made by BB Battery, or equal are recommended (http://www.bb-battery.com/productpages/BP/BP26-12.pdf). Battery housing opens for complete access for installation and maintenance of internal batteries. All battery wiring and installation hardware included, except for batteries. See owner's manual for additional battery dimension and installation information.
Connects to UPS via	Hardwire (contractor supplies wiring to connect battery pack to the UPS - see Owner's Manual for gauge recommendations)
Typical battery lifespan	3-5 years typical (North America)
PHYSICAL	
Shipping weight (lbs)	390
Shipping weight (kg)	177.1
Unit Dimensions (HWD/in)	45.7 x 20.5 x 33.7
Unit Dimensions (HWD/cm)	116.1 x 52.1 x 86.6
Shipping Dimensions (HWD/in)	55.25 x 28.75 x 42.75
Shipping Dimensions (HWD/cm)	140.3 x 73 x 108.6
Unit weight (lbs)	248
Unit weight (kg)	112.6
Material of construction	Steel
Form factors supported	Tower
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?variables.txtModelID=4460.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.